

Technical Data Sheet

NEXT 07 TPU Medium Duty Ducting

- Totally smooth inside to ensure optimization of flow properties.
- Special TPU that combines different properties which make the wall material permanently antistatic (10 Ohms) and resistant to UV.
- Capability of abrasion resistance 20 mm³
- Used extensively in the woodworking, abrasive powders, ceramics and heating and ventilation industries.





Part number	ins Ø Mm	thick Mm	Weight g/m	Bending R. Mm	Vac. m H2O
N7 01 052.0 000.0	50,8	0,70	385	50	2,0
N7 01 060.0 000.0	60	0,70	505	70	1,5
N7 01 063.0 000.0	63,5	0,70	540	70	1,5
N7 01 065.0 000.0	65	0,70	525	75	1,5
N7 01 076.0 000.0	76,2	0,70	615	90	1,5
N7 01 080.0 000.0	80	0,70	645	95	1,5
N7 01 090.0 000.0	90	0,70	720	105	1,0
N7 01 100.0 000.0	100	0,70	860	135	1,0
N7 01 102.0 000.0	102	0,70	880	135	1,0
N7 01 110.0 000.0	110	0,70	945	145	1,0
N7 01 120.0 000.0	120	0,70	1040	160	0,7
N7 01 127.0 000.0	127	0,70	1100	210	0,7
N7 01 140.0 000.0	140	0,70	1120	185	0,5
N7 01 152.0 000.0	152,4	0,70	1345	230	0,5
N7 01 160.0 000.0	160	0,70	1425	250	0,5
N7 01 180.0 000.0	180	0,70	1490	270	0,3
N7 01 203.0 000.0	203,2	0,70	1850	300	0,3
N7 01 254.0 000.0	254	0,70	2685	440	0,2
N7 01 305.0 000.0	305	0,70	4055	530	0,1