



Technical Data Sheet

Vulcano Pu Light Blue Ducting

- Halogen free
- Light and flexible, it is especially suitable for dynamic applications
- Good abrasion resistance
- Inside completely smooth
- Used extensively in the woodworking, abrasive powders, ceramics and heating and ventilation industries.





RUBBER SEALS & GASKETS

| | Ø Ins. mm | Min. wall thick mm | Weight m/g | Vac. mH2O | Bending R. mm | Coil Length m | Volume m³ |
|--------------------------|--------------|--------------------------|---------------|--------------|------------------|---------------------|--------------|
| RY 01 038.0 000.0 | mm | mm | m/g | mH2O | mm | m | m³ |
| RY 01 051.0 000.0 | 38 | 040 | 215 | 20 | 30 | 10/20 | 0,076 |
| RY 01 063.0 000.0 | 51 | 040 | 275 | 1 20 | 40 | 10/20 | 0,108 |
| RY 01 076.0 000.0 | 63 | 040 | 335 | 1 1,7 | 55 | 10/20 | 0,143 |
| RY 01 080.0 000.0 | 76 | 0,43 | 400 | 1 1,7 | 65 | 10/20 | 0,245 |
| RY 01 090.0 000.0 | 80 | 0,43 | 420 | 1 1,6 | 65 | 10/20 | 0,256 |
| RY 01 102.0 000.0 | 90 | 0,43 | 470 | 1 1,6 | 75 | 10/20 | 0,303 |
| RY 01 110.0 000.0 | 102 | 0,53 | 530 | 1 1,3 | 85 | 10/20 | 0,310 |
| RY 01 120.0 000.0 | 110 | 0,53 | 570 | 1 1,2 | 90 | 10/20 | 0,320 |
| RY 01 127.0 000.0 | 120 | 0,53 | 615 | 1 1,0 | 100 | 10/20 | 0,372 |
| RY 01 140.0 000.0 | 127 | 0,53 | 620 | 1,0 | 105 | 10 | 0,405 |
| RY 01 152.0 000.0 | 140 | 0,63 | 840 | 0,8 | 115 | 10 | 0,504 |
| RY 01 160.0 000.0 | 152 | 0,63 | 890 | 0,8 | 125 | 10 | 0,544 |
| RY 01 180.0 000.0 | 160 | 0,63 | 935 | 0,7 | 130 | 10 | 0,622 |
| RY 01 203.0 000.0 | 180 | 0,63 | 1380 | 0,5 | 150 | 10 | 1, 0,855 |
| RY 01 228.0 000.0 | 203 | 063 | 1550 | 0,4 | 165 | 10 | 1, 1,146 |
| RY 01 254.0 000.0 | 228 | 063 | 1740 | 04 | 185 | 10 | 1, 1,170 |
| RY 01 305.0 000.0 | 254 | 0,65 | 1900 | 04 | 210 | 10 | 1 1,188 |
| RY 01 305.0 000.0 | 305 | 0,65 | 2275 | 0,3 | 250 | 10 | 1,613 |
| RY 01 305.0 000.0 | 315 | 0,65 | 2350 | 0,3 | 275 | 10 | 0,662 |